

# Alcogum L 31

## ASE rheology modifier

Alcogum L31 is an acrylate-based emulsion copolymer.

### Specifications

pH	2.2-3.5
Solid content	39-41 %
Viscosity	15000-21000 (2.5% (dry), pH 9.0, NaOH, 25°C, 10 rpm) cps

### Characteristics

Appearance	White emulsion
Density	8.91 lbs/US gal at 25°C
Specific Gravity	1.07 g/cc at 25°C
Viscosity	≤200 cps at 25°C

#### Notes:

Typical Data are based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

## Storage

ALCOGUM L 31 is available in bulk, intermediate bulk and 55-gallon drums. Storage tanks should be plastic, fiberglass, or 316 stainless. Pumps should be low-shear type, such as diaphragm or peristaltic type with all wetted parts and lines being stainless steel, plastic or Teflon. Mild steel, copper, brass and aluminum should not be used. Filtering should be under low shear and volume flow conditions. Freezing should be avoided as it destabilizes the emulsion. The recommended storage temperature is 15-35°C (59-95°F). Dilution or pH adjustment of the product may require additional preservative to prevent biological growth. Keep containers tightly sealed to prevent emulsion from air drying and forming a film. Teflon is a registered trademark of E.I. DuPont De Nemours & Co.

## Safety and handling

ALCOGUM L 31 is listed on the TSCA inventory. Meets FDA requirements under Title 21, Sections 175.105/320, 176.170(\*) and 176.180(\*) Not to exceed 2% by weight in coating solids. Contains no alkylphenol ethoxylate components.

## Additional information

Liquid for ease of handling and metering. Shear thinning flow characteristics. Effective viscosity build in high solids systems. Compatible with anionic and nonionic surfactants. Effective at suspending solid particles >2 microns.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Nouryon, however, makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nouryon does not accept any liability whatsoever arising out of the use of or reliance on this information, or out of the use or the performance of the product. Nothing contained herein shall be construed as granting or extending any license under any patent. Customer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes. The information contained herein supersedes all previously issued information on the subject matter covered. The customer may forward, distribute, and/or photocopy this document only if unaltered and complete, including all of its headers and footers, and should refrain from any unauthorized use. Don't copy this document to a website.

ALCOGUM is a registered trademark in many countries.

## Contact Us

### USA and Canada

Global Headquarters  
Chicago  
USA  
+1 312 544 7000  
ansc-cs@nouryon.com

### China

Regional Headquarters  
Shanghai  
China  
+86 21 2220 5000  
surfactants.asia@nouryon.com

### Europe

Regional Headquarters  
Stenungsund  
Sweden  
+46 303 850 00  
surfactants.europe@nouryon.com

### South East Asia

Regional Headquarters  
Singapore  
+65 6635 5183  
surfactants.asia@nouryon.com

### South America

Regional Sales Office  
Itupeva  
Brazil  
+55 11 4591 8938

The Nouryon logo consists of the word "Nouryon" in a bold, orange, sans-serif font. The letter "N" is stylized with a vertical bar on its left side.