

Aquatreat AR-232

Sodium polymethacrylate

AQUATREAT® AR 232 is a clear amber neutralized aqueous solution of a methacrylic acid polymer.

Specifications

pH	8-9
Solid content	29-31 %
Viscosity	110-375 (25°C, SP# 2, 20 rpm) cps

Notes:

Typical Data are based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Applications

Boiler water dispersant, sludge conditioner.

Safety and handling

AQUATREAT AR-232 meets requirements of 21CFR 173.310.

Additional information

AQUATREAT AR-232 is suggested for use as a desludging agent in water systems such as cooling towers, boilers, and heat exchangers. AQUATREAT AR-232 is used at a rate of 20 ppm for its dispersing action. The amount to be used depends on the system condition and flow pattern in the affected area.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Nouryon, however, makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nouryon does not accept any liability whatsoever arising out of the use of or reliance on this information, or out of the use or the performance of the product. Nothing contained herein shall be construed as granting or extending any license under any patent. Customer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes. The information contained herein supersedes all previously issued information on the subject matter covered. The customer may forward, distribute, and/or photocopy this document only if unaltered and complete, including all of its headers and footers, and should refrain from any unauthorized use. Don't copy this document to a website.

AQUATREAT is a registered trademark in many countries.

Contact Us

USA and Canada

Global Headquarters
Chicago
USA
+1 312 544 7000
ansc-cs@nouryon.com

China

Regional Headquarters
Shanghai
China
+86 21 2220 5000
surfactants.asia@nouryon.com

Europe

Regional Headquarters
Stenungsund
Sweden
+46 303 850 00
surfactants.europe@nouryon.com

South East Asia

Regional Headquarters
Singapore
+65 6635 5183
surfactants.asia@nouryon.com

South America

Regional Sales Office
Itupeva
Brazil
+55 11 4591 8938

The Nouryon logo consists of the word "Nouryon" in a bold, orange, sans-serif font. The letter "N" is stylized with a vertical bar on its left side.