

Aquatreat AR 900A

Polyacrylic acid

Polyacrylic acid, general purpose water treatment
antiscalant

Specifications

Intrinsic viscosity, dl/g 25°C, 0.2N NaCl, pH 7 - 9	0.045-0.070
pH	2.2-3.5
Solid content	49-51 %
Viscosity	50-500 (25°C RVT, 20 rpm) cps

Notes:

Soluble in hot water, acetone, methanol. Partially soluble in cold water. Typical Data are based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Applications

General purpose anti-scalant, dispersant.

Safety and handling

AQUATREAT AR 900A meets requirements of 21CFR 173.310, if fully neutralized with sodium hydroxide.

Additional information

AQUATREAT AR 900A is suggested for use as an antiscalant for calcium carbonate and calcium sulfate, and also functions as a desludger and acid cleaner. The recommended level of application for AQUATREAT AR 900A is 3 to 8 ppm.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Nouryon, however, makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nouryon does not accept any liability whatsoever arising out of the use of or reliance on this information, or out of the use or the performance of the product. Nothing contained herein shall be construed as granting or extending any license under any patent. Customer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes. The information contained herein supersedes all previously issued information on the subject matter covered. The customer may forward, distribute, and/or photocopy this document only if unaltered and complete, including all of its headers and footers, and should refrain from any unauthorized use. Don't copy this document to a website.

AQUATREAT is a registered trademark in many countries.

Contact Us

USA and Canada

Global Headquarters
Chicago
USA
+1 312 544 7000
ansc-cs@nouryon.com

China

Regional Headquarters
Shanghai
China
+86 21 2220 5000
surfactants.asia@nouryon.com

Europe

Regional Headquarters
Stenungsund
Sweden
+46 303 850 00
surfactants.europe@nouryon.com

South East Asia

Regional Headquarters
Singapore
+65 6635 5183
surfactants.asia@nouryon.com

South America

Regional Sales Office
Itupeva
Brazil
+55 11 4591 8938

The Nouryon logo consists of the word "Nouryon" in a bold, orange, sans-serif font. The letter "N" is stylized with a vertical bar on its left side.